



## BELMONDO® Paddock

**Totally robust!  
Gives the rain and wet no chance!**

### Features

The superior quality BELMONDO® Paddock rubber flooring copes well with horse exercise. If the ground is reinforced (asphalt, concrete, paving) the puzzle mat suffices on its own. The latter features a rhomboid profile upper surface and 2 mm pimples on the underside. This allows optimal fluid run-off on both sides.

If the ground is not reinforced, a BELMONDO® plastic grid is also available – as the ideal support plate between the muddy ground and the slip-proof BELMONDO® Paddock rubber floor covering: The grid spacing is specially developed for horses:

The dimensions are calculated so the hooves can neither get stuck nor be forced through the bars. The structure of the grid provides an optimal base i.e. the mat forms a stable covering on top.

- as naturally soft as grassland
- suitable for outdoor use because of ozone- and UV-protection
- highly slip-resistant, even in the wet
- reducing the risk of accidents and injuries (maximum safety even in icy conditions)
- protecting hooves, tendons and joints
- no fluids, no mud: horses stand comfortably dry
- also suitable for stable walkways and washing areas as well as for horse walkers (especially in regions with heavy rainfall, with uncovered areas)
- easy to lay – and very hygienic due to its simple cleaning properties: Sweep with dustpan and brush or clean with high-pressure cleaner

**Consult the separate instructions on laying**



### Data

#### BELMONDO® turn-out area matting:

- Surface:**  
Grooved profile with negative hammer finish
- Underside:**  
Pimpled profile
- Material:**  
Vulcanised rubber
- Dimensions:**  
thickness 19 mm (incl. 2 mm pimples)  
length 1 m  
width 1 m
- Weight per mat:**  
approx. 24 kg
- Puzzle cut on 4 sides**

#### BELMONDO® plastic grid

- Material:**  
Plastic
- Dimensions:**  
thickness 5 cm  
length 79,5 cm  
width 62 cm
- Weight per grid:**  
11 kg

BELMONDO® Paddock can be combined with all new BELMONDO® products

Subject to change without prior notice. All dimensions specified with tolerances: Thickness +2 /-1 mm. Length and width +/- 1.5 % (DIN ISO 3302-1 tolerance class M 4). The tolerances also apply within the mat.